

# NS-6074-F

## O-Ring Lubricant

---

Syn-Tech NS-6074-F is used as an assembly aid to "stick-hold" parts together in multi-component mechanisms such as gear boxes, pumps, and engine accessories. NS-6074-F is also used to "wet out" or lubricate O-rings prior to pressing them into cavities, preventing chafing or tearing. NS-6074-F is a concentrated solution of methacrylate polymer in a synthetic diester based oil which provides lubricity and tack.

### Characteristics:

- Ease of application
- Superior lubricity and tack

### Typical base fluid properties


Viscosity, ASTM D445 @ 100°F, cSt	3267
Viscosity, ASTM D445 @ 210°F, cSt	425
Flash point, ASTM D92, °F	380
Specific gravity, ASTM D1298, 60/60°F	.900 - .930
Total acid number, mg KOH/gm	0.10
*Diluted 3:1 with Plexol 201	

### Material Compatibilities:

Not for use with ABS, polycarbonate, polyester, PPO, or PVC plastics. Not for use on buna S, butyl, or neoprene elastomers. Check with manufacturer or Syn-Tech concerning compatibility.

10/2001 Rev. 2

The information provided herein is offered without warranty, express or implied. Because Syn-Tech does not have control over products it gives as samples or sells, we can't guarantee the suitability of the product for your application. The information above is therefore only to be used as a recommendation.



1433C W. Fullerton Ave.  
Addison, IL 60101 USA

(630) 620-7050  
[www.syn-techlube.com](http://www.syn-techlube.com)