

NS-4313-F

Synthetic Assembly Lubricant

A synthetic hydrocarbon assembly oil formulated to reduce friction and wear during assembly of engine components. Does not contain additives that can cause skin irritation and rashes.

Characteristics:

- Fully synthetic
- Does not contain additives that may cause skin irritation
- 100% compatible with engine oils

Typical Base Fluid Properties

Base fluid	Synthetic Hydrocarbon
Color	Red
ISO Viscosity Grade	680
Viscosity, ASTM D445 @ 40°C, cSt	700
Viscosity Index Extended, ASTM D2270	162
Flash point, ASTM D92, °C (°F)	279(535)
Specific Gravity, ASTM D1298, 20/20°C	.85

Material Compatibilities:

Compatible with most engineering plastics including ABS and polycarbonate. Not for use with Buna S, Butyl, EPDM, EPR, or natural rubber elastomers. Check with material manufacturer or Syn-Tech concerning compatibility.

10/13 Rev.0

The information provided herein is offered without warranty, express or implied. Because Syn-Tech does not have control over products it gives as samples or sells, we can't guarantee the suitability of the product for your application. The information above is therefore only to be used as a recommendation. It should not be used as the basis of a specification. SOF 7.3-01-07 4/28/17



1550F W. Fullerton Ave.
Addison, IL 60101 USA

(630) 628-7290
www.syn-techlube.com

Lubricants that Solve Problems