

## NS-2517-SBO

## Syn-Tech Ltd.

Version No: 1.1 Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

## **SECTION 1 Identification**

#### **Product Identifier**

Product name	NS-2517-SBO		
Synonyms	Not Available		
Other means of identification	Not Available		

#### Recommended use of the chemical and restrictions on use

Relevant identified uses Solid Bearing Oil

#### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party


Registered company name	Syn-Tech Ltd.	Syn-Tech Ltd.		
Address	1550 W Fullerton Ave, Unit F Illinois 60101 United States	1550 W. Fullerton Ave Illinois United States		
Telephone	630-628-7290	630-628-7290		
Fax	Not Available	Not Available		
Website	www.syn-techlube.com	www.syn-techlube.com		
Email	msds@syn-techlube.com	msds@syn-techlube.com		

#### Emergency phone number

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

#### SECTION 2 Hazard(s) identification

# Classification of the substance or mixture NFPA 704 diamond



Issue Date: 08/17/2022

Print Date: 08/17/2022 S.GHS.USA.EN

ersion No: 1.1		Page <b>2</b> of <b>10</b>	Issue Date: 08/17/20
		NS-2517-SBO	Print Date: 08/17/20
H350	May cause cancer.		
Hazard(s) not otherwise classi Not Applicable	fied		
Precautionary statement(s) Pre	evention		
P201	Obtain special instructions b	before use.	
P280	Wear protective gloves and	protective clothing.	
P202	Do not handle until all safet	y precautions have been read and understood	j.
Precautionary statement(s) Re	sponse		
P308+P313	IF exposed or concerned: G	Set medical advice/ attention.	
Precautionary statement(s) Sto	1		
P405	Store locked up.		
Precautionary statement(s) Dis	sposal		
P501	Dispose of contents/contain	er to authorised hazardous or special waste o	collection point in accordance with any local regulation.
Not Applicable SECTION 3 Composition / ir	nformation on ingredie	nts	
Substances See section below for composition Mixtures	of Mixtures		
CAS No	%[weight]	Name	
64742-53-6	0.14	naphthenic distillate, light, hydrotreated (m	ild)
41484-35-9	0.3	thiodiethylene bis(3,5-di-tert-butyl-4-hydrox	
SECTION 4 First-aid measu	res	·	
Description of first aid measur	es		
Eye Contact	Generally not applicable	e.	
Skin Contact	Generally not applicable	e.	
Inhalation	Generally not applicable	е.	
Ingestion	<ul> <li>Generally not applicable.</li> </ul>		

#### Most important symptoms and effects, both acute and delayed

See Section 11

#### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5 Fire-fighting measures**

#### Extinguishing media

- ▶ Foam.
- Dry chemical powder.BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only.

## Special hazards arising from the substrate or mixture

Fire Incompatibility	Fire Incompatibility Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result			
Special protective equipment a	and precautions for fire-fighters			
	Alert Fire Brigade and tell them location and nature of hazard.			
	<ul> <li>Wear breathing apparatus plus protective gloves.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> </ul>			
Fire Fighting	Use water delivered as a fine spray to control fire and cool adjacent area.     Do NOT approach containers suspected to be bot			

• DO NOT approach containers suspected to be hot.

If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use.

Cool fire exposed containers with water spray from a protected location.

Page 3 of 10

#### NS-2517-SBO

	Slight hazard when exposed to heat, flame and oxidisers.
Fire/Explosion Hazard	Combustible. Will burn if ignited. Combustion products include: carbon monoxide (CO) carbon dioxide (CO2) other pyrolysis products typical of burning organic material. May emit poisonous fumes. Articles and manufactured articles may constitute a fire hazard where polymers form their outer layers or where combustible packaging remains in place. Certain substances, found throughout their construction, may degrade or become volatile when heated to high temperatures. This may create a secondary hazard. <b>CARE</b> : Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire.

## **SECTION 6** Accidental release measures

Personal precautions, protective equipment and emergency procedures See section 8

## Environmental precautions

See section 12

#### Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Clean up all spills immediately.</li> <li>Secure load if safe to do so.</li> <li>Bundle/collect recoverable product.</li> <li>Collect remaining material in containers with covers for disposal.</li> </ul>
Major Spills	<ul> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear trill body protective clothing with breathing apparatus.</li> <li>Prevent, by all means available, spillage from entering drains or water courses.</li> <li>Consider evacuation (or protect in place).</li> <li>No smoking, naked lights or ignition sources.</li> <li>Increase ventilation.</li> <li>Stop leak if safe to do so.</li> <li>Water spray or fog may be used to disperse / absorb vapour.</li> <li>Contain or absorb spill with sand, earth or vermiculite.</li> <li>Collect recoverable product into labelled containers for recycling.</li> <li>Collect recoverable product into labelled domainers for recycling.</li> <li>Collect solid residues and seal in labelled drums for disposal.</li> <li>Wash area and prevent runoff into drains.</li> <li>After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.</li> <li>If contamination of drains or waterways occurs, advise emergency services.</li> <li>Minor hazard.</li> <li>Clear area of personnel.</li> <li>Contor personal contact with the substance, by using protective equipment as required.</li> <li>Prevent spillage from entering drains or water ways.</li> <li>Contoriol personal contact with the substance, by using protective equipment as required.</li> <li>Prevent spillage from entering drains or waterways.</li> <li>Collect recoverable product into labelled containers for recycling.</li> <li>Absorb remaining product with sand, earth or vermiculite.</li> <li>Wase and and revuent runoff indins or waterways.</li> <li>If contamination of drains or waterways occurs, advise emergency services.</li> <li>Wase area and prevent runoff indis or waterways.</li> <li>If contamination of drains or waterways occurs, advise emergency services.</li> <li>Wase area and prevent runoff indis or waterways.</li> <li>If contamination of drains or waterways occurs, advise emergency services.</li> <li>Waser ar</li></ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 Handling and storage

Precautions for safe handling	
Safe handling	<ul> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> <li>DO NOT enter confined spaces until atmosphere has been checked.</li> <li>DO NOT enter confined spaces until atmosphere has been checked.</li> <li>DO NOT allow material to contact humans, exposed food or food utensils.</li> <li>Avoid contact with incompatible materials.</li> <li>When handling, DO NOT eat, drink or smoke.</li> <li>Keep containers securely sealed when not in use.</li> <li>Avoid physical damage to containers.</li> <li>Always wash hands with soap and water after handling.</li> </ul>

Page 4 of 10

NS-2517-SBO

	<ul> <li>Work clothes should be laundered separately. Launder contaminated clothing before re-use.</li> <li>Use good occupational work practice.</li> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul>
Other information	Store away from incompatible materials.

## Conditions for safe storage, including any incompatibilities

Suitable container	Generally packaging as originally supplied with the article or manufactured item is sufficient to protect against physical hazards. If repackaging is required ensure the article is intact and does not show signs of wear. As far as is practicably possible, reuse the original packaging or something providing a similar level of protection to both the article and the handler.	
Storage incompatibility	Avoid reaction with oxidising agents	

## SECTION 8 Exposure controls / personal protection

#### **Control parameters**

## Occupational Exposure Limits (OEL)

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Limits (PELs) Table Z-1	naphthenic distillate, light, hydrotreated (mild)	Oil mist, mineral	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	thiodiethylene bis(3,5-di-tert-butyl- 4-hydroxycinnamate)	Particulates Not Otherwise Regulated (PNOR)- Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	thiodiethylene bis(3,5-di-tert-butyl- 4-hydroxycinnamate)	Particulates Not Otherwise Regulated (PNOR)- Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	thiodiethylene bis(3,5-di-tert-butyl- 4-hydroxycinnamate)	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	thiodiethylene bis(3,5-di-tert-butyl- 4-hydroxycinnamate)	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	thiodiethylene bis(3,5-di-tert-butyl- 4-hydroxycinnamate)	Particulates not otherwise regulated	Not Available	Not Available	Not Available	See Appendix D

#### Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3	
naphthenic distillate, light, hydrotreated (mild)	1,100 mg/m3	1,800 mg/m3		40,000 mg/m3	
Ingredient	Original IDLH		Revised IDLH		
naphthenic distillate, light, hydrotreated (mild)	2,500 mg/m3		Not Available		
thiodiethylene bis(3,5-di-tert- butyl-4-hydroxycinnamate)	Not Available		Not Available		

#### Exposure controls

	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.
Appropriate engineering controls	<ul> <li>Employees exposed to confirmed human carcinogens should be authorized to do so by the employer, and work in a regulated area.</li> <li>Work should be undertaken in an isolated system such as a "glove-box". Employees should wash their hands and arms upon completion of the assigned task and before engaging in other activities not associated with the isolated system.</li> <li>Within regulated areas, the carcinogen should be stored in sealed containers, or enclosed in a closed system, including piping systems, with any sample ports or openings closed while the carcinogens are contained within.</li> <li>Open-vessel systems are prohibited.</li> <li>Each operation should be provided with continuous local exhaust ventilation so that air movement is always from ordinary work areas to the operation.</li> <li>Exhaust air should not be discharged to regulated areas, non-regulated areas or the external environment unless decontaminated. Clean make-up air should be introduced in sufficient volume to maintain correct operation of the local exhaust system.</li> <li>For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood. Prior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood.</li> <li>Except for outdoor systems, regulated areas should be maintained under negative pressure (with respect to non-regulated areas).</li> <li>Local exhaust ventilation requires make-up air be supplied in equal volumes to replaced air.</li> <li>Laboratory hoods must be designed and maintained so as to draw air inward at an average linear face velocity of 0.76 m/sec with a minimum of 0.64 m/sec. Design and construction of the fume hood requires that insertion of any portion of the employees body, other than hands and arms, be disallowed.</li> <li>Articles or manufactured items, in their original c</li></ul>

Page 5 of 10

#### NS-2517-SBO

Personal protection	
Eye and face protection	<ul> <li>Safety glasses with side shields</li> <li>Chemical goggles.</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> <li>No special equipment required due to the physical form of the product.</li> </ul>
Skin protection	See Hand protection below
Hands/feet protection	Wear general protective gloves, eg. light weight rubber gloves.
Body protection	See Other protection below
Other protection	<ul> <li>Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent]</li> <li>Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges. A respirator affording higher levels of protection may be substituted. [AS/NZS 1715 or national equivalent]</li> <li>Emergency deluge showers and eyewash fountains, supplied with potable water, should be located near, within sight of, and on the same level with locations where direct exposure is likely.</li> <li>Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels. For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood.</li> <li>Prior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood.</li> <li>Overalls.</li> <li>P.V.C apron.</li> <li>Barrier cream.</li> <li>Skin cleansing cream.</li> <li>Eye wash unit.</li> </ul>

#### **Respiratory protection**

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Respiratory protection not normally required due to the physical form of the product.

#### **SECTION 9** Physical and chemical properties

#### Information on basic physical and chemical properties

Appearance	Red fluid, no odor		
Physical state	Manufactured	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available

#### NS-2517-SBO

Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (Not Available%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

#### SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

#### **SECTION 11 Toxicological information**

#### Information on toxicological effects The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an Inhaled occupational setting. Inhalation of oil droplets or aerosols may cause discomfort and may produce chemical inflammation of the lungs. The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of Ingestion corroborating animal or human evidence The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting Skin Contact Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort Eve characterised by tearing or conjunctival redness (as with windburn). There is ample evidence that this material can be regarded as being able to cause cancer in humans based on experiments and other information. Chronic Repeated application of mildly hydrotreated oils (principally paraffinic), to mouse skin, induced skin tumours; no tumours were induced with severely hydrotreated oils TOXICITY IRRITATION NS-2517-SBO Not Available Not Available TOXICITY IRRITATION Dermal (rabbit) LD50: >2000 mg/kg<sup>[2]</sup> Eye: no adverse effect observed (not irritating)<sup>[1]</sup> naphthenic distillate, light, hydrotreated (mild) Skin (rabbit): 500mg SEVERE Inhalation(Rat) LC50; 2.18 mg/l4h<sup>[2]</sup> Oral (Rat) LD50; >5000 mg/kg<sup>[2]</sup> Skin: no adverse effect observed (not irritating)<sup>[1]</sup> TOXICITY IRRITATION dermal (rat) LD50: >2000 mg/kg<sup>[1]</sup> Eve (rabbit): None\* thiodiethylene bis(3,5-di-tert-Inhalation(Rat) LC50; >6.3 mg/L4h<sup>[2]</sup> Eye: no adverse effect observed (not irritating) $\left[ 1 \right]$ butyl-4-hydroxycinnamate) Oral (Rat) LD50; 6300 mg/kg<sup>[2]</sup> Skin (rabbit): None\*[Ciba-Geigy\*] Skin: no adverse effect observed (not irritating)<sup>[1]</sup> Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.\* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

NAPHTHENIC DISTILLATE, LIGHT, HYDROTREATED (MILD)	are produced from unrefined and mildly refined oils refined base oils, the highly and severely refined dis low mammalian toxicity. Testing of residual oils for m belief that these materials lack biologically active co Toxicity testing has consistently shown that lubricatin s mutagenic and carcinogenic potential correlates w extractables (e.g. IP346 assay), both characteristics For unrefined and mildly refined distillate base oils: Acute toxicity: Animal testing showed high semilethe skin contact, respectively. The same material was a Repeat dose toxicity: Animal testing showed that rep Reproductive / developmental toxicity: No studies oo may reduce the body weight of both the mother and Genetic toxicity: These oils have been found to caus Cancer-causing potential: The general conclusion th however, they have not been found to be associated The material may cause severe skin irritation after p production of vesicles, scaling and thickening of the <b>WARNING:</b> This substance has been classified by t	ted with undesirable components, and rsely related to the degree of processis then of processing will have similar to distillate base oils is inversely related to the highest levels of undesirable con neer-causing and mutation-causing ac by removing or transforming undesiral tillate base oils have a smaller range mutation-causing and cancer-causing n mponents or the components are larg mponents or the components are larg mponents or the components are larg and base oils have low acute toxicities. with its 3-7 ring polycyclic aromatic con that are directly related to the degree al doses of >5000 mg/kg body weight lso reported to be moderately irritating peat dose toxicity was mild to moderat the foetus, and increase the rate of sise mutations. That can be drawn from animal testing i d with an increase in tumours elsewhe rolonged or repeated exposure and m skin. Repeated exposures may produ- the IARC as Group 1: <b>CARCINOGENI</b> lies found in Chinese hamster bone m	d ing; xicities; e oil receives. I to the degree of processing. nponents, have the largest variation of hydrocarbon ctivities. Highly and severely refined distillate base oils ble components. In comparison to unrefined and mildly of hydrocarbon molecules and have demonstrated very potential has shown negative results, supporting the lely non-bioavailable due to their molecular size. Numerous tests have shown that a lubricating base oil npound (PAC) content, and the level of DMSO s/conditions of processing. and >2 g/kg body weight for exposure by swallowing or g to skin, while not being sensitizing. te to the skin. on are available. Animal testing shows that high doses oft tissue malformations. is that these oils may potentially cause skin cancer; and produce on contact skin redness, swelling, the use severe ulceration.
DI-TERT-BUTYL- 4-HYDROXYCINNAMATE)	For thiodiethylenebis(3,5-di-tert-butyl-4-hydroxycinn non-toxic by oral, skin or inhalation exposure. The c long-term effects or increase in mortality. The main of	amate) (TDBHC): Available data from ompound does not cause mutations o	animal testing shows that TDBHC is practically or genetic damage. There do not seem to be any
Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin	×	STOT - Repeated Exposure	×
sensitisation			

Legend: X – Data either not available or does not fill the criteria for classification - Data available to make classification

## **SECTION 12 Ecological information**

	Endpoint	Test Duration (hr)	Species	Value	Source
NS-2517-SBO	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
naphthenic distillate, light, hydrotreated (mild)	ErC50	72h	Algae or other aquatic plants	>1000mg/l	1
	NOEC(ECx)	504h	Crustacea	>1mg/l	1
	EC50	48h	Crustacea	>1000mg/l	1
	EC50	96h	Algae or other aquatic plants	>1000mg/l	1
	Endpoint	Test Duration (hr)	Species	Value	Source
thiodiethylene bis(3,5-di-tert- butyl-4-hydroxycinnamate)	EC0(ECx)	24h	Crustacea	<0.34mg/l	2
	EC50	72h	Algae or other aquatic plants	41mg/l	2
	EC50	48h	Crustacea	>100mg/l	2
	LC50	96h	Fish	>57mg/l	2
Legend:	Ecotox databa		HA Registered Substances - Ecotoxicological Informatic Aquatic Hazard Assessment Data 6. NITE (Japan) - Bio		

## DO NOT discharge into sewer or waterways.

## Persistence and degradability

No Data available for all ingredients No Data available for all ingredients	Ingredient	Persistence: Water/Soil	Persistence: Air
		No Data available for all ingredients	No Data available for all ingredients

#### **Bioaccumulative potential**

Ingredient

## Bioaccumulation Ingredient No Data available for all ingredients Mobility in soil Ingredient Mobility No Data available for all ingredients

### **SECTION 13 Disposal considerations**

Waste treatment methods	
Product / Packaging disposal	<ul> <li>Recycle wherever possible or consult manufacturer for recycling options.</li> <li>Consult State Land Waste Management Authority for disposal.</li> <li>Recycle wherever possible or consult manufacturer for recycling options.</li> <li>Consult State Land Waste Authority for disposal.</li> <li>Bury or incinerate residue at an approved site.</li> <li>Recycle containers if possible, or dispose of in an authorised landfill.</li> </ul>

#### **SECTION 14 Transport information**

Labels Required	
Marine Pollutant	NO
Land transport (DOT): NOT RE	GULATED FOR TRANSPORT OF DANGEROUS GOODS

#### Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

#### Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

#### Transport in bulk according to Annex II of MARPOL and the IBC code

## Not Applicable

#### Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
naphthenic distillate, light, hydrotreated (mild)	Not Available
thiodiethylene bis(3,5-di-tert- butyl-4-hydroxycinnamate)	Not Available

#### Transport in bulk in accordance with the ICG Code

Product name	Ship Type
naphthenic distillate, light, hydrotreated (mild)	Not Available
thiodiethylene bis(3,5-di-tert- butyl-4-hydroxycinnamate)	Not Available

Carcinogens

#### **SECTION 15 Regulatory information**

#### Safety, health and environmental regulations / legislation specific for the substance or mixture

#### naphthenic distillate, light, hydrotreated (mild) is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List	
---	--

International Agency for Research on Cancer (IARC) - Agents Classified by the	he IARC
Monographs	

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US - Massachusetts - Right To Know Listed Chemicals

thiodiethylene bis(3,5-di-tert-butyl-4-hydroxycinnamate) is found on the following regulatory lists US OSHA Permissible Exposure Limits (PELs) Table Z-1 US OSHA Permissible Exposure Limits (PELs) Table Z-3

US DOE Temporary Emergency Exposure Limits (TEELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US National Toxicology Program (NTP) 15th Report Part A Known to be Human

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

US TSCA Chemical Substance Inventory - Interim List of Active Substances

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for Air Pollutants Other Than PM-2.5

US NIOSH Recommended Exposure Limits (RELs)

#### **Federal Regulations**

NS-2517-SBO

#### Section 311/312 hazard categories

Sociel of the lade goldes	
Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Dxidizer (Liquid, Solid or Gas)	No
Drganic Peroxide	No
Self-reactive	No
n contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	Yes
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	
Serious eye damage or eye irritation	
Specific target organ toxicity (single or repeated exposure)	
Aspiration Hazard	
Germ cell mutagenicity	
Simple Asphyxiant	
Hazards Not Otherwise Classified	

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4) None Reported

#### State Regulations

## US. California Proposition 65

WARNING: This product can expose you to chemicals including naphthenic distillate, light, hydrotreated (mild), which are known to the State of California to cause cancer. For more information, go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>.

#### **National Inventory Status**

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (naphthenic distillate, light, hydrotreated (mild); thiodiethylene bis(3,5-di-tert-butyl-4-hydroxycinnamate))
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (naphthenic distillate, light, hydrotreated (mild))
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

#### **SECTION 16 Other information**

Revision Date	08/17/2022
Initial Date	08/18/2022

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

end of SDS

#### Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit。 IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.