

NS-1517-F

Rust Preventive Oil

NS-1517-F is a mineral oil based rust preventive oil for outdoor and marine environments. Forms a stable, thin film for long term protection. Does not contain nitrites, amines, chlorides or barium compounds.

Characteristics:

- Protects ferrous metals against rust
- Excellent protection in marine environments
- Will not gell when exposed to water
- Will not polymerize or harden over time.
- Removable with mineral spirits

Typical Properties

Color	Amber
Viscosity, ASTM D445 @ 20°C, cSt	20
Density, 20°C, g/cc	.857
Flash Point, ASTM D92, °C(F°)	>105(221)
Aromatic Content, %	<0.5
Pour point, ASTM D97, °C	<-30

Material Compatibilities:

Compatible with most engineering plastics (including ABS and polycarbonate) and elastomers. Check with material manufacturer or Syn-Tech concerning compatibility.

06/17 Rev.0

The information provided herein is offered without warranty, express or implied. Because Syn-Tech does not have control over products it gives as samples or sells, we can't guarantee the suitability of the product for your application. The information above is therefore only to be used as a recommendation. It should not be used as the basis of a specification. SOF 7.3-01-07 4/28/17



1550F W. Fullerton Ave.
Addison, IL 60101 USA
(630) 628-7290
www.syn-techlube.com

Lubricants that Solve Problems