

# NS-4238-FG

## Noise Damping Grease

---

NS-4238-FG is a semi-synthetic PTFE enhanced specialty grease designed for exceptional noise and vibration damping characteristics. Suitable for open and closed gears, cables, slides and bearings. This product exhibits good oxidation stability and anti-wear properties.

This product does not contain silicone fluid.

### Characteristics:

- Excellent anti-wear properties
- Soft for ease of application
- High oxidation stability
- High noise and vibration damping
- Operating temperature range of -20°F to +250°F
- PTFE enhanced

### Typical Properties

Thickener	Li Complex
NLGI grade	1
Penetration, ASTM D1403, worked, 60 Ds	340
Dropping point, ASTM D2265, °F, min.	500
Oil Separation, ASTM D6184-98, 24 hrs. @ 212°F, %	5
Specific gravity, 60/60°F	.902

### Typical Base Fluid Properties

Base fluid	Synthetic blend
------------	-----------------

### Material Compatibilities:

Compatible with most engineering grade plastics and elastomers including ABS, polycarbonate and Modified PPO plastics. Check with manufacturer or Syn-Tech concerning compatibility information.

10/06 Rev.2

The information provided herein is offered without warranty, express or implied. Because Syn-Tech does not have control over products it gives as samples or sells, we can't guarantee the suitability of the product for your application. The information above is therefore only to be used as a recommendation. It should not be used as the basis of a specification. SOF 7.3-01-07 4/28/17



---

1550F W. Fullerton Ave.  
Addison, IL 60101 USA  
(630) 628-7290  
[www.syn-techlube.com](http://www.syn-techlube.com)

**Lubricants that Solve Problems**